



Accessories



Universal utility software (US)
 (for retrieving data from counter memory into a PC via an RS-232 cable and for controlling the counter with a PC)


1 CFM isoprobe on tripod



Relative humidity / temperature sensor
 Range 10-90%
 Accuracy ± 3%
 Relative humidity
 Range 0-100°F (Centigrade opt.)
 Accuracy ± 0.3%



High pressure diffuser



Air velocity sensor
 Range 80-120 feet per minute (standard)
 0-200 feet per minute (optional)
 0-300 feet per minute (optional)
 Accuracy ± 2%



Specifications

Size Channels	0.3 Micron
	2 ch
	4 ch
	5 ch
	6 ch
0.5 Micron	2 ch
	4 ch
	5 ch
	6 ch
	0.3, 0.5, 1.0, 5.0, 10.0
	0.3, 0.5, 1.0, 3.0, 5.0, 10.0
	0.3, 0.5, 1.0, 5.0
	0.5, 5.0
	0.5, 1.0, 5.0, 10.0
	0.5, 0.7, 1.0, 5.0, 10.0
	0.5, 0.7, 1.0, 3.0, 5.0, 10.0
Light Source	Laser diode (30,000 hours mean time between failure)
Outputs	RS232, RS485 serial interface
Sample Time	1 second to 24 hours
Alarm Counts	1-9,999,999
Location Labels	0-999, appear on printout
Data Storage	400 Samples

Ordering Guide

Size	11.2" wide x 6.0" high x 18" deep (28.4 x 15.2 x 45.7 cm)
Weight	24 pounds (10.9 kg)
Environment	Operating 55-105°F (12-41°C) noncondensing 20-95% relative humidity.
Storage	40-160°F (9-40-70°C) noncondensing up to 98% relative humidity.
Number of size channels	2-6
Built-in printer	with or without
Power	100VAC, 115VAC, 220VAC, 240VAC

When ordering, specify Model A2408 and:

Minimum Threshold 0.3 or 0.5 micron
 Setting